



PRODUCT INFORMATION

Lubricants - Agricultural

Version: UAE47/01

Valvoline™ UNITRAC L 80W

Unitrac L is a premium multi-purpose fluid designed for year-round service in tractor hydraulic systems, transmissions, and differentials with wet brake systems. The product is not designed for use as an engine lubricant. Valvoline Unitrac L protects against wear and corrosion of tractor components and has excellent friction properties.

(Gear oil viscosity SAE 80W is approximately motor oil viscosity SAE 10W-30).

Performance levels
John Deere J20C, J20D
Massey Ferguson: M1145,
Massey Ferguson: M1143, M1135
Ford M2C86B, C
Ford M2C134D
CNH MAT 3525, 3526
API GL-4
Allison C-4
CAT TO-2
Volvo WB101
Parker HF-2
Kubota UDT
Steiger SEMS
WHITE Q-1826
Volvo (VCE 97303*)

Applications

This product is for universal tractor lubrication; gearbox, differential, hydraulic system and wet brakes, not for the engine.

The products friction properties are adjusted to the use in differentials with wet brakes. Earthmoving machines and Forklifts of the latest generation now use Unitrac L 80W for their differentials with wet brakes.

The product is suitable for use in applications like mowers, balers, and plows with hydraulic activation. Always check if the oil of the external equipment can be mixed with the oil of the tractor.

Also combine harvesters use Unitrac L 80W in their transmissions, hydraulic systems and final drives.

Features & Benefits

Wear protection

Valvoline Unitrac L 80W (10W-30) is specially formulated for agricultural use, adjusted to different circumstances like low speed/high torque. The carefully chosen base oils and additive system form a protective oil film for all the tractor components.

Tractor component cleanliness

Detergent and dispersant additives keep the gearbox, differential, and hydraulic system clean and in good condition. The oil is resistant against moist and oxidation.

Multi-Purpose

Valvoline Unitrac L 80W (10W-30) can be used for the gearbox, the differential, and the hydraulic system. A real multipurpose use. An extra advantage is one oil for several components and less storage; no miss-applications.

Break Down resistance

Thermal and Oxidation stable oil film. Special Extreme Pressure additives protect the tractor components against break down.



PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit

www.valvolineeurope.com

For all OEM specifications visit:

<https://pisheets.valvoline.com>

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Unitrac	
SAE Viscosity Grade	80W (10W-30)
Viscosity, mm²/s @ 100 °C. ASTM D-445	9.215
Viscosity, mm²/s @ 40 °C. ASTM D-445	51.43
Viscosity Index ASTM D-2270	163
TBN, mg KOH/g ASTM D-2896	8.48
Pour Point, °C ASTM D-5949	-39
Specific Gravity @ 15.6°C. ASTM D-4052	0,873
Flash Point, COC, °C. ASTM D-92	228

**This information only applies to products manufactured in the following location(s):
UAE**

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet

<http://sds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –

™ Trademark of Valvoline, registered in various countries © 2022

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.