

# PRODUCT INFORMATION



*Automotive Chemicals – Technical Sprays - Protection*

Version: **TS/016**

## **Valvoline™ V-Belt Spray**

High quality spray to protect V-Belts and prevent them from slipping.

---

### **Applications**

Vehicles  
Conveyer belts  
Drill presses  
Lathes  
Generators  
Forklift trucks  
Milling machines  
Machinery  
Agricultural Machinery  
Concrete mixers  
Lawn mowers  
Compressors  
Pumps

### **Product characteristics**

User friendly  
Remedies and prevents slipping and creaking  
Excellent adhesion properties  
Lasting protection  
Dilatant  
Resistant to weather influences  
Conditions V-Belts  
Delays the wear of V-Belts  
Directed jet spray

### Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ V-Belt Spray should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Switch off engine.

Apply Valvoline™ V-Belt Spray in an equal, thin layer on the threads of the V-Belt and allow to take effect.

After evaporation of the product, the engine can be switched on.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineeurope.com](http://www.valvolineeurope.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ V-Belt Spray	
Contents	500 ml
Basis	Polyalphaolefine
VOC-content	Approx. 93% w/w
Colour	Transparent
Scent	Characteristic
Relative density at 20°C	0,89 g/ml
Yield	1,15 g/sec
Vapour pressure at 20°C	3 to 4 bar

**This information only applies to products manufactured in the following location(s): Europe**

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

## Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.