



PRODUCT INFORMATION

Lubricants - Engine Oil - Passenger Car Motor Oils

Version: 069/01

Valvoline™ SynPower™ ENV C2/C3 5W-30

VALVOLINE SynPower – OEM Approved Premium Grade Synthetic Motor Oil.
Formulated for ultimate performance and protection under all operating conditions, SynPower is designed to fulfil the latest standards of leading engine manufacturers.

OEM Approvals

MB-Approval 229.52

MB-Approval 229.51

Renault RN17

PSA B71 2290

Performance Levels

ACEA C2, C3, A5/B5

API SP, SN PLUS, SN

MB-226.52

MB-229.31

Renault RN 0700 / 0710

Meets the requirements of Fiat 9.55535-S1, -S3

Applications

Specially formulated for use in modern engines, reduces exhaust emissions and improves fuel efficiency. Protects against low speed pre ignition (LSPI).

Suitable for use in the Peugeot-Citroën group.

Suitable for cars with environmentally friendly exhaust systems, like EGR and TWC, DPF, GPF and can also be used where Renault RN0700 or RN710 is required in the 5W-30 viscosity grade.

Check owner's manual.

Features & Benefits

Ultimate protection and performance

SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers and protects against low speed pre ignition.

Engine cleanliness

Keeps engine extremely clean by minimizing deposits.

Optimized for emission control systems

Specifically designed for use with emission control systems like DPF (Diesel Particulate Filter) and TWC (Three Way Catalyst). Low SAPS output makes the emission control system in optimal conditions.

Excellent cold start performance

Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Wear protection

Provides ultimate protection against wear under all operating conditions.



PRODUCT INFORMATION

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit
<https://www.valvolineglobal.com/en-eur/> or
<http://pisheets.valvolineglobal.com>

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

| SynPower ENV C2/C3 Motor Oil | |
|--|--------|
| SAE Viscosity Grade | 5W-30 |
| Viscosity, mm²/s @ 100°C | 12.0 |
| ASTM D-445 | |
| Viscosity, mm²/s @ 40°C | 70.5 |
| ASTM D-445 | |
| Viscosity Index | 169 |
| ASTM D-2270 | |
| Viscosity, mPa.s -30°C | < 6400 |
| ASTM D-5293 | |
| TBN, mg KOH/g | 8.4 |
| ASTM D-2896 | |
| Pour Point, °C | -42 |
| ASTM D-5949 | |
| Specific Gravity @ 15.6°C | 0.851 |
| ASTM D-4052 | |
| Flash Point, COC, °C | 240 |
| ASTM D-92 | |

This information only applies to products manufactured in the following location(s):
Europe

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet

<http://sds.valvolineglobal.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –

™ Trademark, Valvoline Global Operations ©2025 Valvoline Global Operations

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.